



# Weatherstrip Attachment Tape 5404

Technical Data Sheet

April 2009


Supersedes Technical Data Sheet dated August 2004

**General Description** 3M™ Weatherstrip Attachment Tape 5404 is a 1.2 mm thick, medium-density, gray acrylic foam tape constructed with two different adhesives. The heat-activated adhesive forms an immediate, consistent and durable bond to most EPDM formulations and Santoprene® materials. The pressure-sensitive adhesive is characterized by high adhesion and holding strength to many surfaces, including automotive paints and metals. This tape has good conformability and is used to attach weatherstrip and/or gasket seals for automotive and industrial applications.

**Shelf Life** One year from date of receipt by customer when stored at 4°C - 38°C (40°F - 100°F) and 0-95% relative humidity (RH). The optimum storage conditions are 22°C (72°F) and 50% relative humidity.

**Product Construction**

Heat-activated E2 adhesive  
 Gray acrylic foam core  
 Pressure-sensitive AR-7 acrylic adhesive  
 Liner



**Physical Properties**

Values shown are typical values not to be used for specification purposes.

Tape thickness (excluding liner)	1.20 mm ± 0.10 mm (0.047 inch ± 0.004 inch)
Tape density (excluding liner)	690 kg/m <sup>3</sup> ± 65 kg/m <sup>3</sup> (43 lb/ft <sup>3</sup> ± 4 lb/ft <sup>3</sup> )
Tabbing option	3M™ Tabbing Tape 5400

**Roll Width and Length**

3M™ Weatherstrip Attachment Tapes are available in the following standard widths. Millimeter widths are rounded to the nearest whole numbers (7, 8, 9 mm . . .) and 1/8 inch increments starting with 1/4 inch (0.25, 0.375, 0.50, 0.625 inch . . .).

Minimum widths:  
4 mm Levelwound  
5 mm Planetary

Roll Width	Roll Width Tolerance	Roll Length (maximum)
Planetary Rolls		
5 – 6 mm (0.197 – 0.236 in.)	+/- 0.40 mm (+/-0.015 in.)	66 meters (72 yards)
6.35 – 9.5 mm (0.25 – 0.375 in.)	+/- 0.40 mm (+/-0.015 in.)	99 meters (108 yards)
10 – 18 mm (0.394 – 0.709 in.)	+/- 0.40 mm (+/-0.015 in.)	132 meters (144 yards)
> 18 mm (> 0.709 in.)	+/- 0.80 mm (+/- 0.031 in.)	132 meters (144 yards)
Levelwound Rolls		
4 – 16 mm (0.157 – 0.630 in.)	+/- 0.40 mm (+/-0.015 in.)	900 meters (984 yards)



Authorized Distributor,  
Converter, and Fabricator  
www.jbc-tech.com

# Technical Data Sheet


## 3M™ Weatherstrip Attachment Tape 5404

Page 2


### Performance Properties

#### 90° Peel Adhesion

Typical performance of 3M™ Weatherstrip Attachment Tape 5404 is shown below. Peel values depend on the composition and cross-section of a particular weatherstrip. These values should be for reference only.



#### 90° Peel Adhesion



3M Acrylic Foam Tape 5404 has excellent initial adhesion at assembly and long-term adhesion over all environmental conditions during vehicle life.

#### Contact Information

The information provided in this technical document is intended as a guide for this product. For more information or help in selecting a 3M product for an application, please contact 3M HELPS at 1-888-3M HELPS (1-888-364-3577).

#### Regulatory

IMDS# 336083. This is a published material entry on [www.mdsystem.com](http://www.mdsystem.com).

Santoprene® is a Registered Trademark of AES.

3M is a Trademark of 3M Company.

**Technical Information:** The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

**Product Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

**Warranty, Limited Remedy, and Disclaimer:** Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. (make sure enough space around 3M logo)



#### Automotive Division

3M Center, Building 223-1S-02  
St. Paul, MN 55144-1000  
[www.3M.com/autosolutions](http://www.3M.com/autosolutions)

© 3M 2009  
75-3467-9991-1  
Printed in the U.S.A.



ISO/TS 16949:2002  
File No. A2109