

Product Data Sheet

CONTENTS				
Face	1/16" polyethylene foam		PRODUCT DESCRIPTION	
Adhesive	Medical grade, pressure-sensitive acrylic		DM-5002 is a white polyethylene foam. It is coated on one side with a medical grade, acrylic adhesive and supplied on a paper liner.	
Backing	Silicone coated one-side, 78 lb basis weight		SPLICES	
FACE PROPERTIES			Splices on tape and liner are functional in that they are intended for continuous process conditions.	
Thickness	1/16 in		STANDARD LABELING	
Tensile Strength	MD	141 psi	Materials will have core labeling stating the part number, roll number, lot number, width, and linear feet per roll. <i>Note: Any additional labeling requirements should be noted at time of order entry.</i>	
	Test Method: ASTM D-3575			
Elongation	MD	314%	TRACEABILITY	
	Test Method: ASTM D-3575		Material traceability must comply with current Good Manufacturing Practices. Each shipment of material will contain a lot number, which is traceable through production records. Certificate of Conformance will accompany each shipment.	
Typical substrate values of uncoated materials				
ADHESIVE PROPERTIES			STORAGE CONDITIONS	
Peel Adhesion	>1500 g/in		Store in original protective packaging at temperatures between 50-80°F and 40-60% RH.	
2mil PET	Test Method: DMT-PSTC-1			
Polyken Probe Tack	650 g/in ²		APPEARANCE	
2mil PET	Test Method: ASTM D-2979		Virtually free from foreign and dark colored matter.	
Loop Tack	2450 g/in ²		ROLL DIMENSIONS	
2mil PET	Test Method: PSTC-16		Smaller roll length by request.	
Shelf Life	TBD		Length	600 linear feet max.
Thickness	1.9 mil		Width	59 inch max.
Biocompatibility	Cytotoxicity	Pass	Core	3 inch inside diameter
	Primary Dermal	Pass	Issue Date: June 1, 1998	
	Buehler	Pass	Revision Date: February 23, 2016	

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment, and end use. Typical values are not intended to be used for specification development. All data is subject to change, as DermaMed deems appropriate.

CONFIDENTIAL

381 Geneva Avenue * Tallmadge, OH 44278
271 Progress Boulevard * Kent, OH 44240
Tel:330-633-8216 * Fax: 330-633-2461

UNCONTROLLED COPY