

Topper-Seal Foam Technical Data Sheet



Authorized Distributor,
Converter, and Fabricator
www.jbc-tech.com



DESCRIPTION

Foam Seal Topper-Seal is a low density industrial PVC foam.

APPLICATIONS

Foam Seal Topper-Seal is an economical tape for use as a seal between pickup truck caps and body side rail. Topper-Seal remains pliable at temperatures of -20°C to 78°C.

STORAGE

Product shelf life begins on the date of production as referenced by the lot number. Foam Seal Topper-Seal has a shelf life of 6 months when stored at or below 75°F.

ADDITIONAL INFORMATION

Foam Seal/Novagard believes that the information provided is a true and accurate description of the typical characteristics of the aforementioned product; however, it is the responsibility of the individual user to thoroughly test the product in their specific application to determine performance, efficacy, and safety.

PRODUCT SPECIFICATIONS*

Parameter	Condition	Specification
Gauge (Thickness)	3/16" to 1/4"	+/- 10%
Width (Rolls)	1.5" to < 2.5" wide	+/- 1/16"
Length	< 50' long	0" to +6"
Density (lbs/cu ft)		5.5 – 9.0
Adhesion	Stainless steel	12 oz / in minimum Typical value: >30 oz/in

* Specifications based on a sample size of three to five. Testing to these specifications may be dependent on the specific application. Specifications are subject to change without notice.

TYPICAL PROPERTIES

	Test Method	Typical Values
Hardness (Shore "00")	ASTM D2240	25
Force to Compress @ 25 %	ASTM D1667	3.0 psi
Compression Deflection	ASTM D1667	2.0 psi
Water Absorption	ASTM D1056	6 %
Tensile Strength (psi)	ASTM D412	20
Elongation (%) With Adhesive	ASTM D412	110 %
Flammability	MVSS 302	Self-Extinguishing

The information provided in the above table is not intended for use in preparing specifications. Information for reference is intended as a general guideline only. Typical values based on a sample size of three to five and performed within 2 weeks of manufacture.