

RTS15DC

DOUBLE COATED TISSUE ACRYLIC ADHESIVE TAPE

PRODUCT DESCRIPTION

Double Coated Tape

RTS15DC is a double coated tissue tape coated on both sides with a rubber adhesive. The tissue carrier is easily hand torn. Designed for general purpose bonding applications, the product provides reliable, cost effective, permanent bonds on a wide variety of materials. RTS15DC is supplied on a white polycoated kraft release liner.

FEATURES & BENEFITS

- Aggressive, quick-stick rubber adhesive
- Excellent adhesion, tack and shear properties
- Versatile and cost-effective
- Conformable, hand tearable tissue carrier
- Bonds to a wide variety of materials, including metals, glass, ceramics, foams and plastics

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value		Typical Value (Metric)		Test Method
Product Thickness (Total)	3.70	mils	0.094	mm	PSTC-133
Adhesive Thickness (Liner Side)	1.50	mils	0.038	mm	PSTC-133
Carrier Thickness	0.70	mils	0.018	mm	PSTC-133
Adhesive Thickness (Exposed Side)	1.50	mils	0.038	mm	PSTC-133
Peel Adhesion	60	oz/in	16.67	N/25mm	PSTC-101
Tack	52	oz	1474	g	ASTM D 2979
Shear Adhesion	24	hrs @ 2.2 psi	24	hrs @15.2 kPa	PSTC-107
Tensile Strength	1	lb/in	4	N/25mm	PSTC-131
Elongation	-	%	-	%	
Minimum Service Temperature	-20	°F	-29	°C	
Maximum Service Temperature	160	°F	71	°C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

8/5/2022

