



FT 8380


Avery Dennison™ FT 8380 was designed for use on bonding point-of-purchase display information to shelving materials.

FEATURES

- Specially formulated rubber based adhesive
- Polyester carrier
- Densified kraft release liner

BENEFITS

- Clean removability from painted metal, glass and aluminum
- Excellent cold temperature performance



CONSTRUCTION:

Liner:

60# White Kraft

Adhesive 1:

Rubber

Carrier:

Polyester

Adhesive 2:

Rubber

FT 8380

Adhesive Properties:		Typical Values		
Thickness	ASTM D3652	US Mils	MM's	Micron's (µm)
Liner		3.5	0.09	89
Adhesive 1 - Liner		1.6	0.04	41
Carrier		0.5	0.01	13
Adhesive 2 - Unwind		1.2	0.03	30
Total Caliper without Liner:		3.3	0.08	84
Total Caliper:		6.8	0.17	173

Peel Adhesion		ASTM D3330		
180° 12 in (305 mm) / min				
Substrate			Lbf / In	N / Meter
SS	Liner	Initial	4.0	704
PP	Liner	Initial	3.3	581
Painted Metal	Liner	Initial	2.5	440
Aluminum	Liner	Initial	2.9	511
Glass	Liner	Initial	3.8	669

Loop Tack		ASTM D6195		
180° 20 in (508 mm) / min				
Substrate			Lbf / In	N / Meter
SS	Liner	Initial	5.0	881
	Unwind		18.8	3,311

Static Shear		ASTM D3654		
180° 1/2" sq (3.25 cm2) 1000 g @ Room Temp				
Substrate			Mins to Fail	
SS	Liner	Initial	> 230	

TEMPERATURES	° F	° C
Minimum Application Temperature	20° F	-7° C
Maximum Continuous Operating Temperature	200° F	93° C
Maximum Intermittent Operating Temperature	225° F	105° C

THE LISTED VALUES ARE TYPICAL AND NOT INTENDED TO SERVE AS PRODUCT SPECIFICATIONS

APPLICATION TECHNIQUES

- It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

STORAGE / SHELF LIFE

- One year when stored at 64-72°F (18-22°C) / 30-70% relative humidity, out of direct sunlight and in original packaging.

Please refer to Tapes.AveryDennison.com for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2020 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Asia Pacific
Kunshan, China,
NO. 618 Nanhe Road
Kunshan Economic &
Technological Zone
China, 215335
Phone: +86 512 57155001
Fax: +86 512 57155059

Europe
Tieblokkenlaan 1
B-2300 Turnhout
Belgium
Phone: +32 (0)14 40 48 11
Fax: +32 (0)14 40 48 55

North America
250 Chester Street
Painesville, Ohio
44077 USA
Phone: +1 866-462-8379
Fax: +1 888-358-4469