



SC Metallized Polypropylene Film

Coatings Company, LLC

			ta S		

	VU:11	TENTS	- 1	PRODUCT DESCRIPTION		
Face		arlized OPP film	DM-7201 is a white, pearlized OPP (oriented polypropylene) film, metallized on one side. It is			
Adhesive	Medical grade	, pressure-sensitive	coated on one side with a medical grade, rubber- based adhesive and supplied on a paper liner.			
Backing	Silicone coate	d one-side, 78 lb ba	SPLICES			
	FACE PF	ROPERTIES	Splices on tape and liner are functional in that they			
	-			are intended for continuous process conditions.		
Thickness			1.1 mil	STANDARD LABELING Materials will have core labeling stating the part		
Tensile Strength		MD CD	13130 psi 28806 psi	number, roll number, lot number, width, and linear feet per roll. Note: Any additional labeling require-		
	Test Method:	ASTM D-882		ments should be noted at time of order entry.		
Тур	oical substrate valu	es of uncoated materials	TRACEABILITY			
	ADHESIVE	PROPERTIES	- 1	Material traceability must comply with current Good		
Peel Adhesion 2mil PET Test Method: DMT		DMT-PSTC-1	>1600 g/in	Manufacturing Practices. Each shipment of material will contain a lot number, which is traceable through production records. Certificate of Conformance will accompany each shipment.		
Polyken Prob		ASTM D-2979	450 g/in²	STORAGE CONDITIONS		
Loop Tack	Test Method:		5500 g/in²	Store in original protective packaging at temperatures between 50-80°F and 40-60% RH.		
Shelf Life			TBD	APPEARANCE Virtually free from foreign and dark colored matter.		
See "Storage Con	ditions		and the second seco	ROLL DIMENSIONS *Smaller roll length by request. Length 2000 linear feet max.		
Thickness			1.1 mil	Width 59 inch max. Core 3 inch inside diameter		
Biocompatibi	lity	Cytotoxicity Primary Dermal	Pass Pass	issue Date: January 19, 2009		
		Buehler	Pass	Revision Date: May 2, 2016		

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment, and end use. Typical values are not intended to be used for specification development. All data is subject to change, as DermaMed deems appropriate.

381 Geneva Avenue * Tallmadge, OH 44278

271 Progress Boulevard * Kent, OH 44240

Tel:330-633-8216 * Fax: 330-633-2461

UNCONTROLLED COPY