

# 1232PR

1/32" WHITE POLYETHYLENE DOUBLE COATED PERMANENT REMOVABLE

## PRODUCT DESCRIPTION

### Double Coated Tape

1232PR is a 1/32" thick white closed cell, crosslinked polyethylene foam coated with a permanent, high performance rubber based adhesive on the exposed side and a removable rubber based adhesive on the liner side. The product is supplied on a white glassine paper liner.

## FEATURES & BENEFITS

- High immediate bond on exposed side
- Repositionability and clean removal on liner side
- Great chemical resistance
- Low compression set

## PRODUCT CONSTRUCTION



## PRODUCT SPECIFICATIONS

Test	Side	Typical Value	Typical Value (Metric)	Test Method
Product Thickness (Total)		33.9 mils	0.861 mm	PSTC-133
Adhesive Thickness	(LN)	1.1 mils	0.028 mm	PSTC-133
Carrier Thickness		31.0 mils	0.787 mm	PSTC-133
Adhesive Thickness	(EX)	1.8 mils	0.046 mm	PSTC-133
Peel Adhesion	(LN)	30 oz/in	8.33 N/25mm	PSTC-101
	(EX)	111* oz/in	30.84 N/25mm	PSTC-101
Tack	(LN)	23 oz	650 g	ASTM D2979
	(EX)	38 oz	1077 g	ASTM D2979
Shear Adhesion	(LN)	>24 hrs @ 2.2 psi	>24 hrs@15.2kPa	PSTC-107
	(EX)	>168 hrs @ 2.2 psi	>168 hrs@15.2kPa	PSTC-107
Normal Tensile		56 lb/in	39 N/cm2	
Min. Service Temperature		-20 °F	-29 °C	
Max. Service Temperature		160 °F	71 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

\*Peel Adhesion max value is recorded as a result of foam destruction during test

## Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street  
Easthampton, MA 01027

413-527-7120 Main  
800-356-3572 Toll Free U.S.

[www.adhesiveapps.com](http://www.adhesiveapps.com)

**Adhesive**  
Applications™

08-17-2022

