



Product Data Sheet

CONTENTS				
Face	Polyester spunlaced fabric		PRODUCT DESCRIPTION	
Adhesive	Medical grade, pressure-sensitive acrylic		DM-2095 is a white, spunlaced polyester nonwoven tape coated on one side with a medical grade, acrylic adhesive and supplied on a paper liner.	
Backing	Silicone coated one-side, 54 lb basis weight		SPLICES Green tape only	
FACE PROPERTIES			Splices on tape and liner are functional in that they are intended for continuous process conditions.	
Basis Weight		1.34 oz/yd ²	STANDARD LABELING	
	Test Method: ASTM D-3776		Materials will have core labeling stating the part number, roll number, lot number, width, and linear feet per roll. <i>Note: Any additional labeling requirements should be noted at time of order entry.</i>	
Grab Strength	CD	14.8 lbs	TRACEABILITY	
	MD	26.5 lbs	Material traceability must comply with current Good Manufacturing Practices. Each shipment of material will contain a lot number, which is traceable through production records. Certificate of Conformance will accompany each shipment.	
	Test Method: ASTM D-5034		STORAGE CONDITIONS	
	Typical substrate values of uncoated materials.		Store in original protective packaging at temperatures between 50-80°F and 40-60% RH.	
ADHESIVE PROPERTIES			APPEARANCE	
Peel Adhesion		>1300 g/in	Virtually free from foreign and dark colored matter.	
	Test Method: DMT-PSTC-1		ROLL DIMENSIONS Smaller roll length by request.	
Polyken Probe Tack		300 g/in ²	Length	TBD linear feet max.
	Test Method: ASTM D-2979		Width	59 inch max.
Loop Tack		750 g/in ²	Core	3 inch inside diameter
	Test Method: PSTC-16		Issue Date: September 25, 2020	
Shelf Life		24 Months	Revision Date: Original	
See "Storage Conditions"	Real-Time age testing study			
Thickness		2.4 mil		
Biocompatibility	Cytotoxicity	Pass		
	Primary Dermal	Pass		
	Buehler	Pass		

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment, and end use. Typical values are not intended to be used for specification development. All data is subject to change, as DermaMed deems appropriate.

CONFIDENTIAL

381 Geneva Avenue * Tallmadge, OH 44278
271 Progress Boulevard * Kent, OH 44240
Tel:330-633-8216 * Fax: 330-633-2461