

CONFIDENTIAL

DM-8010

UNCONTROLLED COPY

Single Coated Polyethylene Film

Product Data Sheet

CONTENTS				
Face	3 mil polyethylene			PRODUCT DESCRIPTION DM-8010 is a clear polyethylene film with a matte
Adhesive	Medical grade, pressure-sensitive acrylic			finish. It is coated on one side with a medical grade, acrylic adhesive and supplied on a paper liner.
Backing	king Silicone coated one-side, 78 lb basis weight			SPLICES
FACE PROPERTIES				Splices on tape and liner are functional in that they
Thickness			3.0 mil	are intended for continuous process conditions.
Tensile Strength Test Method: Elongation		MD CD ASTM D-882 MD	2300 psi 2000 psi 475%	STANDARD LABELING Materials will have core labeling stating the part number, roll number, lot number, width, and linear feet per roll. Note: Any additional labeling requirements should be noted at time of order entry.
	Tost Mothod:	CD ASTM D-882	550%	TRACEABILITY Material traceability must comply with current Good
				Manufacturing Practices. Each shipment of material
Typical substrate values of uncoated materials.				will contain a lot number, which is traceable through production records. Certificate of Conformance will accompany each shipment.
ADHESIVE PROPERTIES				
Peel Adhesio		DMT-PSTC-1	>1100 g/in	STORAGE CONDITIONS Store in original protective packaging at
Polyken Prol		ASTM D-2979	550 g/in ²	temperatures between 50-80°F and 40-60% RH. APPEARANCE
Loop Tack	Test Method:	PSTC-16	1950 g/in ²	Virtually free from foreign and dark colored matter.
Shelf Life			TBD	ROLL DIMENSIONS Smaller roll length by request. Length 900 linear feet max. Width 59 inch max.
Thickness			1.7 mil	Core 3 inch inside diameter
Biocompatib	ility	Cytotoxicity Primary Dermal	Pass Pass	Issue Date: April 17, 2003
		Buehler	Pass	Revision Date: May 9, 2016

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment, and end use. Typical values are not intended to be used for specification development. All data is subject to change, as DermaMed deems appropriate.

381 Geneva Avenue * Tallmadge, OH 44278

271 Progress Boulevard * Kent, OH 44240

Tel:330-633-8216 * Fax: 330-633-2461