

Product Data Sheet

CONTENTS		
Face	Polyester spunlaced fabric	
Adhesive	Medical grade, pressure-sensitive acrylic	
Backing	Silicone coated one-side, 54 lb basis weight	
FACE PROPERTIES		
Basis Weight	1.34 oz/yd ²	
	Test Method: ASTM D-3776	
Grab Strength	CD	14.8 lbs
	MD	26.5 lbs
	Test Method: ASTM D-5034	
	Typical substrate values of uncoated materials.	
ADHESIVE PROPERTIES		
Peel Adhesion	>1100 g/in	
	Test Method: DMT-PSTC-1	
Polyken Probe Tack	170 g/in ²	
	Test Method: ASTM D-2979	
Loop Tack	630 g/in ²	
	Test Method: PSTC-16	
Liner Release	>20g	
	Test Method: DMT-LR	
Coat Weight	2.15 ± 0.2 g/100in ²	
	Test Method: DMT-CWT	
Thickness	1.3 mil	
Biocompatibility	Cytotoxicity	Pass
	Primary Dermal	Pass
	Buehler	Pass
PRODUCT DESCRIPTION		
DM-2001C is a white, spunlaced polyester nonwoven tape. It is coated on one side with a medical grade, acrylic adhesive and supplied on a paper liner.		
SPLICES Green tape only		
Splices on tape and liner are functional in that they are intended for continuous process conditions.		
STANDARD LABELING		
Materials will have core labeling stating the part number, roll number, lot number, width, and linear feet per roll. <i>Note: Any additional labeling requirements should be noted at time of order entry.</i>		
TRACEABILITY		
Material traceability must comply with current Good Manufacturing Practices. Each shipment of material will contain a lot number, which is traceable through production records. Certificate of Conformance will accompany each shipment.		
STORAGE CONDITIONS		
Store in original protective packaging at temperatures between 50-80°F and 40-60% RH.		
APPEARANCE		
Virtually free from foreign and dark colored matter.		
ROLL DIMENSIONS Smaller roll length by request.		
	Length	2000 linear feet max.
	Width	59 inch max.
	Core	3 inch inside diameter
Issue Date:		March 12, 2014
Revision Date:		November 17, 2015

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment, and end use. Typical values are not intended to be used for specification development. All data is subject to change, as DermaMed deems appropriate.

CONFIDENTIAL

381 Geneva Avenue * Tallmadge, OH 44278
271 Progress Boulevard * Kent, OH 44240
Tel:330-633-8216 * Fax: 330-633-2461

UNCONTROLLED COPY