

7316B

1/16" BLACK POLYETHYLENE DOUBLE COATED FOAM TAPE

PRODUCT DESCRIPTION


Double Coated Tape

7316B is a 1/16" thick black closed cell, crosslinked polyethylene foam coated on both sides with a high performance acrylic based adhesive with an easy release 4.5 mil blue poly liner.

FEATURES & BENEFITS

- Easily die cut
- Low application temperature
- Great chemical resistance
- Low compression set
- Better conformability, cushioning. & vibration damping

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value		Typical Value (Metric)		Test Method
Product Thickness (Total)	66.50	mils	1.689	mm	PSTC-133
Adhesive Thickness (Liner Side)	2.00	mils	0.051	mm	PSTC-133
Carrier Thickness	62.50	mils	1.588	mm	PSTC-133
Adhesive Thickness (Exposed Side)	2.00	mils	0.051	mm	PSTC-133
Peel Adhesion	90	oz/in	25.00	N/25mm	PSTC-101
Tack	39	oz	1106	g	ASTM D 2979
Shear Adhesion	>24	hrs @ 2.2 psi	>24	hrs @15.2 kPa	PSTC-107
Tensile Strength	113	lb/in	495	N/25mm	PSTC-131
Elongation	228	%	228	%	
Minimum Service Temperature	10	°F	-12	°C	
Maximum Service Temperature	180	°F	82	°C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

Rev A

7/24/2018

